SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

KONTAKT IPA

Registration number

P83X-38PV-Q00Y-QEHD UFI:

Synonyms None.

BDS000792AE **Product code** 19-May-2021 Issue date

Version number 2.0

Revision date 17-March-2022 Supersedes date 19-May-2021

1.2. Relevant identified uses of the substance or mixture and uses advised against

Cleaners - Precision Identified uses

None known. Uses advised against

1.3. Details of the supplier of the safety data sheet

Company name CRC Industries Europe by

Address Touwslagerstraat 1

> 9240 Zele Belgium

Telephone +32(0)52/45.60.11

> hse@crcind.com www.crcind.com

Company name CRC Industries UK Ltd.

Wylds Road **Address**

> Castlefield Industrial Estate TA6 4DD Bridgwater Somerset

United Kingdom

Telephone +44 1278 727200 Fax +44 1278 425644 E-mail hse.uk@crcind.com www.crcind.com Website

1.4. Emergency telephone

Tel.:(+44)(0)1278 72 7200 (office hours: 9-17h CET)

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

H222 - Extremely flammable Aerosols Category 1

aerosol.

H229 - Pressurized container: May

H336 - May cause drowsiness or

burst if heated.

Health hazards

Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Category 3 narcotic effects Specific target organ toxicity - single

exposure

dizziness

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Propan-2-ol; Isopropyl alcohol; Isopropanol

Hazard pictograms



Signal word Danger

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

Prevention

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing mist/vapours.

P271 Use only outdoors or in a well-ventilated area.

Response Not assigned.

Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or

Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

Mixture

General information

| Chemical name | % | CAS-No. / EC No. | REACH Registration No. | Index No. | Notes |
|---|----------------|------------------------|------------------------|--------------|-------|
| Propan-2-ol; Isopropyl alcohol; Isopropanol | 75 - 100 | 67-63-0 200-661-7 | 01-2119457558-25 | 603-117-00-0 | # |
| Classification | on: Flam. Liq. | 2;H225, Eye Irrit. 2;H | 1319, STOT SE 3;H336 | | |
| Carbon dioxide | 1 - 5 | 124-38-9 204-696-9 | - | - | # |
| Classification | on: Press. Gas | s;H280 | | | |

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

ATE: Acute toxicity estimate.

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

Extremely flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing media

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters Special protective

equipment for firefighters Special fire fighting procedures

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. This product is miscible in water. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4 Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

| Components | Type | Value | |
|---|------|-------------|--|
| Carbon dioxide (CAS 124-38-9) | STEL | 27400 mg/m3 | |
| | | 15000 ppm | |
| | TWA | 9150 mg/m3 | |
| | | 5000 ppm | |
| Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) | STEL | 1250 mg/m3 | |
| | | 500 ppm | |
| | TWA | 999 mg/m3 | |
| | | 400 ppm | |

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

Follow standard monitoring procedures.

procedures

Derived no effect levels (DNELs)

General Population

| Components | Value | Assessment factor | Notes |
|--|------------------|-------------------|------------------------|
| Propan-2-ol; Isopropyl alcohol; Isopropand | ol (CAS 67-63-0) | | |
| Long-term, Systemic, Dermal | 319 mg/kg bw/day | 2 | Repeated dose toxicity |
| Long-term, Systemic, Inhalation | 89 mg/m3 | 2 | Repeated dose toxicity |
| Long-term, Systemic, Oral | 26 mg/kg bw/day | 2 | Repeated dose toxicity |
| <u>Workers</u> | | | |
| Components | Value | Assessment factor | Notes |
| Propan-2-ol; Isopropyl alcohol; Isopropand | ol (CAS 67-63-0) | | |
| Long-term, Systemic, Dermal | 888 mg/kg bw/day | 1 | |
| Long-term, Systemic, Inhalation | 500 mg/m3 | 1 | |
| dicted no effect concentrations (PNECs) | | | |
| Components | Value | Assessment factor | Notes |

| Components | Value | Assessment | factor Notes | |
|--|----------------------|------------|--------------|--|
| Propan-2-ol; Isopropyl alcohol; Isopro | ppanol (CAS 67-63-0) | | | |
| Freshwater | 140.9 mg/l | 1 | | |
| Secondary poisoning | 160 mg/kg | 30 | Oral | |
| Sediment (freshwater) | 552 mg/kg | | | |
| Soil | 28 mg/kg | | | |

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

Skin protection

- Hand protection When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough

time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Neoprene gloves are

recommended. Suitable gloves can be recommended by the glove supplier.

- Other Not available.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with

organic vapour cartridge and full facepiece. (Filter type A)

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

Material name: KONTAKT IPA - Kontakt chemie - Europe

BDS000792AE Version #: 2.0 Revision date: 17-March-2022 Issue date: 19-May-2021

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid.
Form Aerosol.
Colour Colourless.
Odour Alcohol.
Odour threshold Not available.
pH Not applicable.

Melting point/freezing point -89 °C (-128.2 °F) estimated

Initial boiling point and boiling

range

82 °C (179.6 °F)

Flash point 12.0 °C (53.6 °F) Closed cup

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

2 %

Flammability limit - upper 12 %

(%)

Vapour pressure 43 mbar at 20°C

Vapour density 2.1

Relative density 0.8 at 20°C

Solubility(ies)

Solubility (water)

Auto-ignition temperature

Decomposition temperature

Viscosity

Explosive properties

Oxidising properties

Soluble in water
425 °C (797 °F)
Not available.
Not available.
Not explosive.
Not oxidising.

9.2. Other information

VOC 760 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid high temperatures.

10.5. Incompatible materials Acids. Strong oxidising agents. Chlorine. Isocyanates.

10.6. Hazardous Carbon oxides.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Eye contact Causes serious eye irritation.

Skin contact Based on available data, the classification criteria are not met.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components Species Test Results

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Acute Inhalation

LC50 Rat > 25000 mg/m3, 6 h

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Not likely, due to the form of the product.

Mixture versus substance

information

Not available.

SECTION 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Aquatic

Acute

Crustacea LC50 Brine shrimp (Artemia salina) > 10000 mg/l, 24 hours
Fish LC50 Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Propan-2-ol; Isopropyl alcohol; Isopropanol 0.05

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Other adverse effectsThe product contains volatile organic compounds which have a photochemical ozone creation

potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

EU waste codeThe Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1950

14.2. UN proper shipping AEROSOLS, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Hazard No. (ADR) Not available.

Tunnel restriction code D

14.4. Packing group Not available.

14.5. Environmental hazards No

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

RID

14.1. UN number UN1950

14.2. UN proper shipping AEROSOLS, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

14.4. Packing group Not available.

14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number UN1950

14.2. UN proper shipping AEROSOLS, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

14.4. Packing group Not available.

14.5. Environmental hazards No

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN1950

14.2. UN proper shipping Aerosols, flammable

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -

14.4. Packing group Not available.

14.5. Environmental hazards No **ERG Code** 10L

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

Other information

Passenger and cargo Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

14.1. UN number UN1950

14.2. UN proper shipping Aerosols, flammable

name

Material name: KONTAKT IPA - Kontakt chemie - Europe
BDS000792AE Version #: 2.0 Revision date: 17-March-2022 Issue date: 19-May-2021

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk -

14.4. Packing group Not available.

14.5. Environmental hazards

Marine pollutant No EmS F-D, S-U

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

14.7. Transport in bulk Not established.

according to Annex II of MARPOL 73/78 and the IBC

Code

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Carbon dioxide (CAS 124-38-9)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert - Germany).

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.

CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No. 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals). RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement

The classification for health and environmental hazards is derived by a combination of calculation

International concernant le transport de marchandises dangereuses par chemin de fer). RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value.

VME: Exposure Average Value. VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

References

Information on evaluation method leading to the classification of mixture

Full text of any H-statements not written out in full under Sections 2 to 15

methods and test data, if available.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Revision information

Product and Company Identification: EU Poison Centre

Composition / Information on Ingredients: Component Summary

SECTION 3: Composition/information on ingredients: Component information SECTION 8: Exposure controls/personal protection: Eye/face protection SECTION 8: Exposure controls/personal protection: Respiratory protection

Physical & Chemical Properties: Multiple Properties

SECTION 12: Ecological information: Endocrine disrupting properties

Transport Information: Material Transportation Information

SECTION 15: Regulatory information: France SECTION 16: Other information: Disclaimer

Training information

Disclaimer

Follow training instructions when handling this material.

CRC Industries Europe byba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

BDS000792AE Version #: 2.0 Revision date: 17-March-2022 Issue date: 19-May-2021